



BOTTICELLI USB

The Last Generation Modem

56K (V.90, K56Flex) multimedia USB modem

USB interface for PC & Mac users

V.80 Video Conferencing ready

SpeakerPhone

High speed Internet access over PSTN

Fax & Voice mail

Answering machine

Flash Eprom upgradable



BOTTICELLI USB is the multimedia modem for every application that requires ultra high speed and reliability over a remote user analog line.

The USB interface guarantees the maximum data throughput and a real Plug & Play for an external device. The modem is powered directly by the USB line: no other power supply is requested.

BOTTICELLI USB offers a complete solution of data, fax, voice and video communication for professional, office or home users. One of the most typical application is the Internet access where BOTTICELLI USB permits to increase dramatically the receive data throughput from the ISPs to the remote user.

BOTTICELLI USB uses the V.90 modulation scheme for 56Kbps line speed and the previous ITU-T standards from 33,6Kbps to 2,4Kbps; in any case the modem is able to recognize the ITU-T standard of the other side modem and to select the maximum interoperability speed.

BOTTICELLI USB is the ideal solution for the SOHO application: it can be used as a digital speakerphone, a complete voice fax mail server, a sophisticated digital answering machine.

The modem supports V.80 (H.324) VideoReady standard for the VideoConferencing over PSTN.

The package is completed by a very powerful and multilanguage data/fax/voice application for Windows® 98.

Main Feature

- Multimedia data/fax/voice modem at 56kbps and 33,6Kbps
- Modulation standard: V.90, K56FLEX, V34, V32bis, V32, V22bis
- Speakerphone: full duplex digital phone with echo canceller
- Fax on demand, Voice mail boxes, message broadcasting
- Send and receive fax: 9600bps and 14.400bps (V.17)
- Error correction according to MNP4-10 and ITU-T V.42
- Error compression according to MNP 5 and ITU-T V.42bis
- High speed USB port
- Power supply directly from USB port
- Headset and speaker output
- Dimensions: 165 x 112 x 25,5 mm
- Including software for Windows® 98

