

GSM/GPRS Modem

POCKET GPRS MICRO C QB - Code 8D5690QB

- **GSM/GPRS** serial modem
- **Data, SMS** applications
- Class 10 GPRS
- **Remote management** of any serial device

Integrated Microprocessor

DESCRIPTION

Pocket GPRS Micro C QB is a **GSM/GPRS serial modem** suitable for **Data and SMS applications**.

It is the evolution of Digicom GSM/GPRS terminals that in the last years gained the trust of several installers of wireless applications.

Pocket GPRS Micro C QB is equipped with a **microprocessor** for an easier installation in industrial applications, **especially when used with PLC**, meters, presence detectors or similar.

It can be **used in any application where the traditional phone line is not available** but **where it is necessary to have a DATA connection** to access and remote control the installation or to connect and transfer the data between the center and the remote site.

If you haven't many information to send, we suggest to use the SMS management to send data with Pocket GPRS Micro C QB at a low cost.

The Micro application integrated into Pocket GPRS Micro C QB will not influence the standard operation with GSM devices; it will improve the installation allowing the **remote configuration via SMS** and the control of the GSM network quality via SMS.

You can really go on using the software applications you normally use without worrying about any incompatibility with AT commands as eventual AT commands not foreseen in the software can be **managed directly by the microprocessor as additional strings**. The AT commands not recognized by the GSM module will be correctly executed by the micro without any ERROR message.

No more "device cannot be reached" message with the GSM network automatic search and the registration periodic update to the GSM network set by the user.

Pocket GPRS Micro C QB is the **ideal solution even with devices working with Operating Systems**: from Windows® to Macintosh up to the several Linux distributions.

The design is compact and rugged; it is made of aluminum with winglets for the wall mounting; these features makes the **product suitable also in the most extreme solutions of industrial environments**.



POCKET GPRS MICRO C QB 19/02/2013

For further information visit our website <http://www.digicom.it>

Pocket GPRS Micro C QB can be also fixed on a DIN rail, purchasing the “**DIN rail Pocket Kit**” accessory (Code 8D5720).

The **power cabling** uses the same connectors of automotive solutions to guarantee the maximum reliability even in critical applications (crash, vibrations, etc.) The power range is wider, **from 5 to 32Vdc** with a considerable low consumption so that Pocket GPRS Micro C QB can be used in various applications without modifications. Also a power supply through solar panels can be taken into considerations.

The data interface is a 9 pin **RS232 (V.24/V.28) serial interface** able to control the interface speed from 1200 to 115.200 bps, as for a standard modem.

The SIM slot (Plug-In 3V and 1.8V) and the **SIM Holder** have been developed for an easy installation and maintenance.

Besides **V.32 protocol** for data connections with analog modem at 9600bps, Pocket GPRS Micro C QB also supports the **V.110 digital protocol** for ISDN connections.

Both **PDU and Text SMS** can be managed.

With the **Class 10 GPRS** you will have 4 channels (timeslots) to receive data and 2 timeslots to send information. You will be able to increase the downstream speed up to 85 Kbps and the upstream up to 42 Kbps. You will be **always connected but you will pay for the transferred data only**.

On request, it is possible to carry out **special version** of Pocket GPRS Micro C QB allowing the use of Class 10 GPRS (4+2) with the **TCP/IP protocol**.

TECHNICAL FEATURES

- 850/900/1800/1900MHz Quad-band modem
- Class 10 GPRS
- Standard ETSI GSM Phase 2+ compliant
- Radio GSM 850/900 MHz Class 4 (2W output power)
- Radio DCS 1800/1900MHz Class 1 (1W output power)
- External Antenna with 3 meters cable (SMA connector)
- AT commands support (GSM 07.07 and 07.05)
- Windows® 7, Vista, XP, 2000 supported
- MAC OS 10.4.9 or higher supported
- Linux supported
- Internal microprocessor management
- Data transmission up to 9600 bps
- Analog protocols management: V.32, V.22bis, V.22, V.21
- ISDN protocol management: V.110
- Non Transparent Mode (RLP)
- PDU and Text mode SMS (MT/MO)
- Plug-in (3 - 1.8V) SIM slot
- 9 pin RS232 data interface (V24/V28)
- Led indicators: power and GSM
- Power supply: from 5 to 32 Vcc
- Low consumption
- Size: 87 x 75 x 25 mm
- Weight: 130 gr
- Temperature range: -20°C/+55°C
- R&TTE Approval
- CE Mark

Package content

- Pocket GPRS Micro C QB
- External antenna with 3 meters cable
- Serial cable
- Power supply
- Quick guide for the configuration

