## Tintoretto FRAD

## DESCRIPTION

Tintoretto FRAD is a flexible and high performing multiprotocol Bridge/Router ideal for the TCP/IP Internetworking, point-to-point over leased line up to 2Mbps. It operates both with public and private leased lines (HDSL, CDN/CDA, Baseband, Voice)

In Frame Relay operation, Tintoretto FRAD can handle up to 20 logical channels connecting simultaneously 20 different remote LANs. It is Autolearning for and easier and faster setup.

Tintoretto FRAD is suitable for any application. It has a universal WAN interface, that can be setup by the user via RS232, V.35 or X.21.

It supports multiple functionalities like Bridging, IP/IPX Routing, NAT (LAN and WAN), NAT Export, Default Export, DHCP Server and Relay, Syslog, Secondary IP Address and other.

A powerful built-in Firewall takes care of the secutiry. Any undesired access to LAN resources is blocked or filtered. It is possible to program the Firewall for stations, protocols, ports, addresses, etc.

Tintoretto FRAD is ready to use. It is supplied with preconfigured profiles and the installation quick guide.

Code: 8E4053

TINTORETTO FRA

- TCP/IP and IPX Bridge Router
- IP Routing, IPX Routing, Transparent Bridge, Autolearn and Spanninf Tree Bridge
- Connects to the LAN
- LAN to LAN over CDN leased lines, CDA, HDSL
- WAN V.35, V.24 or X.21 interfaces
- Frame Relay:RFC1490 protocol support for Multivendor Interoperability
- Up to 20 DLCI logical channels supported
- Firewall Security function
- CHAP, PAP Authentication
- Syslog function for log transmission to LAN stations
- Log and statistics on LAN and Wan for any protocol
- Password protected configuration
- Local configuration via terminal and remote configuration via Telnet, TFTP or SNMP
- Supported protocols: PPP, MLPPP, IPCP, IPXCP, CCP, BCP, NAT, NAPT, Reverse NAPT, DHCP Server/Relay, BOOTP Relay, PAP, CHAP, CLI, RIP I, RIP II, Demand RIP, SNMP MIB I, MIB II, MIB Enterprise
- LAN 10BT (UTP) for Hub connection
- LAN 10BT (UTP) for PC connection
- LAN Speed: 10Mbps
- WAN Speed: up to 2 Mbps
- Flash upgradable

Fast and secure connections between LANs over leased lines (CDN, CDA, HDSL) for medium and small offices (SOHO).



For further information: international@digicom.it or http://www.digicom.it